



Low VOCs
Repels Dirt & Dust
Repels Water & Oil
Enhances Concrete Color
Resists Staining & Discoloration
Works Over Water-based or Acid Stains

OIL, WATER & STAIN REPELLANT PENETRATING SEALER

SharkSeal™ is a water and oil repellent penetrating sealer with color enhancing properties based on a blend of complex resins including nano-enhanced fluoropolymers. It penetrates deep into porous surfaces such as interior or exterior concrete, stone and pavers, yet is compatible as an enhancing sealer over NewLook color stains. Easily clean surfaces with SharkSeal™ as it repels dirt, dust and resists stains from most common spills including dirty auto fluids, beverages and many other fluids. SharkSeal has low VOC's and will not blush or yellow. Prolongs the life of concrete affected by winter freeze-thaw cycle and salt intrusion. SharkSeal™ is breathable, dries quickly, with strong abrasion and chemical resistance, and good hot/wet tire pickup resistance. It also enhances the color of the substrate when it is applied in two wet-on-wet coats.

SharkSeal™ works great for surfaces that require a higher-end, yet cost-effective finish that holds up very well to traffic such as in industrial floors, driveways, garage floors, retail and restaurant floors, etc. Performs very well over decorative concrete including stained and stamped concrete, overlays, natural/manufactured porous stone, pavers and exposed aggregate.

Surface Preparation

Surface must be completely clean and dry. All debris, loose concrete, coatings, dust, grease, paints, oils, release, wax, etc. must be removed. At a minimum, for exterior surfaces proper pressure washing is required to help open concrete pores and remove obstructing particles, which includes, but is not limited to: dust, dirt, and curing residue. If pressure washing is not an option, such as interior areas, alternative preparation methods may be required: light acid – (use EcoAcid™ or QuickEtch™), grinding, stripping, etching, wet vacuuming, etc. If muriatic acid is used, flush the surface with clean water and neutralize. Allow surface to dry completely.

Coverage

Unsealed Surfaces: 200 to 300 ft² (18 – 27 m²) per gallon
Stained or Sealed Surfaces: 300 to 400 ft² (27 – 37 m²) per gallon

Application

Mix thoroughly before using. Apply heavy to the point of rejection with two wet-on-wet coats achieving approximately 200 – 300 square feet (18 – 27 square meters) using a pump or airless sprayer, or with a brush, low-nap roller or microfiber pad on tighter surfaces. If over-application occurs, immediately thin out with brush or roller. Apply coating only when air and surface temperature is between 50°F (10°C) rising and 90°F (32°C) and cooling. Apply second coat immediately after first is penetrated into the surface. SharkSeal dries to a clear finish.




NEWLOOK
GETNEWLOOK.COM



OIL, WATER & STAIN REPELLANT PENETRATING SEALER




REPELS OIL



REPELS WATER



LOW VOC



**REDUCES
FREEZE/THAW**



**REPELS
DIRT & DUST**

- Indoor & Outdoor Use
- Enhances Surface Color
- Resists Staining & Discoloration
- Non-Yellowing or Blushing
- Use on Concrete, Stone & Pavers
- Works Over Water-based or Acid Stains

How it Works

SharkSeal™ is a water and oil repellant penetrating sealer with color enhancing properties. It is designed to penetrate deeply into porous surfaces such as interior or exterior concrete, stone and pavers, yet is compatible as an enhancing sealer over NewLook color stains.

